



Aastra 6725ip and 6721ip

IP phones for Microsoft® Lync™

Aastra's 6725ip and 6721ip IP phones for Microsoft Lync, are the latest additions to our award winning line of IP phones.

Embedded in our renowned hardware design is the Microsoft Lync 2010 Phone Edition, offering seamless integration to Microsoft's Lync Server 2010. This combination provides for the fullest Lync feature set available, including simplified installation, management and configuration.

Whether you choose the 6725ip with its "Better Together" desktop link, or the entry level 6721ip, both models are designed for everyday desktop use and include dual Gigabit Ethernet ports and message waiting light indicators.

Aastra 6725ip

The 6725ip is a true IP phone that can operate as a standalone Microsoft Lync endpoint. When connected to a Microsoft Lync 2010 equipped desktop, it provides a synchronized integration with the desktop client enabling enhanced functionality, including click-to-dial and desktop control of calling features such as transfer, hold, call park and conferencing. The 6725ip features both a full color 3.5" LCD screen and a separate Unified Communications (UC) presence icon providing direct access to features and presence indications in Lync. Exceptional voice quality is provided through the use of Microsoft audio codecs in both the handset and hands-free modes.

Aastra 6721ip

The 6721ip is unique to the Aastra Lync model line, and provides a lower cost option for users who still require the benefits of a true IP phone, including dual Gigabit Ethernet ports and message waiting light indicator – but do not require the full UC desktop integration capabilities of the 6725ip. The 6721ip is an ideal selection for Hot-desking applications and common areas, such as lobbies and meeting rooms.



Aastra 6725ip



Aastra 6721ip

Benefits:

✦ "Always on" Operation

It is no longer necessary to have a phone connected to an operating PC to enjoy the benefits of Lync. Both models of Aastra's Microsoft Lync phones are true stand-alone IP phones and have the Microsoft Lync 2010 Phone Edition embedded in the phone. The 6725ip has the additional advantage of being able to be connected to a local desktop PC via a USB cable, enabling desktop PC phone control, multi-media call escalation and synchronized PC and phone locking.

✦ Intuitive Interface

An ergonomic and user friendly hard key layout, used in conjunction with selectable soft keys, a large 2-way navigation key and a 3.5" LCD display screen, provide an efficient and intuitive interface.

✦ UC Presence Indicator

The 6725ip includes a large presence indicator displaying, at a glance, your own presence status being shown to other Lync users.

✦ Simplified Deployments

Both models are designed to save your business time and money. Dual auto-sensing switched Gigabit Ethernet ports eliminate additional wiring and simplify installations without compromising the bandwidth required by "power users". Integrated IEEE 802.3af Power-over-Ethernet allows easy deployment with centralized powering and backup.

	6725ip	6721ip
Screen UI	3.5" QVGA color	3.5" QVGA color
2-way Nav Key + Select Key	•	•
2 LCD softkeys + Menu Key	•	•
Home + Back Keys	•	•
Wideband Audio Handset	•	•
Wideband Speakerphone	•	•
Wideband Headset Support	•	•
Network Connectivity	2 x 10/100/1000 BaseT Ethernet	2 x 10/100/1000 BaseT Ethernet
USB Type A Ports	1	0
USB Type B Ports	1	0
UC Presence Indicator	•	•
Message Waiting Indicator	•	•
Power Options		
PoE Support	•	•
Optional AC Adapter	•	•

Feature Keys and other Interfaces

- 3 selectable soft keys
- Headset and speakerphone keys (6725ip only)
- RJ headset jack (6725ip only)
- Home and back keys
- Message waiting light indicator
- 2-way navigation key
- 2 volume keys
- Full numerical keypad (0-9, #,*)

Display and Indicators

- 3.5" QVGA Color Screen LCD
- Intuitive graphical user interface and navigation menus
- Multi-color presence indicator
- Dedicated LED for call and message waiting indicator

Power

- Integrated IEEE 802.3af Power-over-Ethernet (PoE) support
- AC adapter (48V DC) sold separately

Operating conditions

- Temperature: 0°C to 50°C (32°F to 122°F)
- Relative Humidity: 20% to 90%, noncondensing
- Storage Temperature: -20°C to 70°C (-4°F to 158°F)

Supported Languages*

- English
- Chinese Simplified, Chinese Traditional, Danish, Dutch, Finnish, French, German,

Italian, Japanese, Korean, Norwegian, Portuguese (Brazil), Russian, Spanish, Swedish *

Regulatory

- CE /Europe
- ROHS compliant
- WEEE (2002/96/EC)
- CE Mark (2004/108/EC EMC Directive and 73/23/EEC Low Voltage Directive)

EMC

- FCC Part 15 Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B

Safety

- CAN/CSA C22.2 No. 60950/ UL 60950-1
- EN 60950
- AS/NZS 60950
- CB scheme

Telecom/RF

- FCC Part 68 (Hearing Aid Compatibility)

Part Numbers

- Aastra 6725ip: A6725-0131-20-55
- Aastra 6721ip: A6721-0131-20-55

Recommended Power Adapters

- North American: D0023-1051-02-75
- International: D0023-1051-00-75

Accessories

- High Angle Stand: D0080-1659-00-75

* Available December 2010



About Aastra

Aastra Technologies Limited (TSX:AAH) is a global company at the forefront of the Enterprise Communication market. Headquartered in Concord, Ontario, Canada, Aastra develops and delivers innovative and integrated solutions that address the communication needs of businesses small and large around the world. Aastra enables Enterprises to communicate and collaborate more efficiently and effectively by offering customers a full range of open standard IP-based and traditional communications networking products, including terminals, systems, and applications. For additional information on Aastra, visit our website at www.aastra.com



Aastra 6725ip with optional High Angle Stand

Aastra Technologies
155 Snow Blvd.
Concord, Ont., L4K 4N9 - Canada
T 1 905 760 4200
F 1 905 760 4233
www.aastra.com

Aastra USA
2811 Internet Blvd.
Frisco, Texas 75034
T 1 800 468 3266
F 1 469 365 3006
www.aastrausa.com

Rev. 29.09.10



Copyright © 2010 Aastra Technologies Ltd. All rights reserved. Information in this document is subject to change without notice. Aastra assumes no responsibility for any errors that may appear in this document. Product capabilities described in this document pertain solely to Aastra's marketing activities in the U.S. and Canada. Availability in other markets may vary.

