

MAXAttach™ | Wireless

Dual-Unit Wireless Tabletop Conference Phone System

The industry's first dual-phone wireless tabletop conferencing system. MAXAttach Wireless provides expanded wireless coverage for medium sized conference rooms, delivering clear, full-duplex audio through two complete phone units – all with no cables in the way.

ClearOne.



UNRIVALED WIRELESS
AUDIO QUALITY,
ROOM COVERAGE
AND FLEXIBILITY

MAXATTACH WIRELESS APPLICATIONS

- Executive Office
- Medium Conference Room
- Any Room Without a Phone Line

MAXATTACH WIRELESS ADVANTAGES

Superior Audio Performance

- + Distributed Echo Cancellation® effectively eliminates echo
- + Noise cancellation removes background noises from fans or HVAC systems
- + Full-duplex sound enables participants to speak and listen at the same time without cutting in and out
- + Automatic level controls keep participants' audio balanced and consistent
- + First-mic priority eliminates hollow "tunnel" sound by activating only the microphone closest to the person speaking
- + Three microphones in each phone unit provide 360° audio pickup
- + ClearEffect™ provides natural, full-sounding audio without requiring wideband on both ends

Wireless Capabilities

- + Turn any room into a conference room, even one without a phone line
- + Wireless signal range allows use in multiple rooms without moving the base unit
- + Wireless design provides a clean look with no wires on the table or floor
- + 12 hours of talk time allows for lengthy conferences without recharging; 36 hours of standby time reduces recharging frequency; automatic power-save mode conserves battery life
- + Dual-function power supply/charger enables conferencing while charging
- + Digital spread spectrum technology with 64-bit encryption ensures secure conferencing
- + Audible warnings sound when phone is out of range or needs charging
- + Phone paging button allows easy identification of phone's location

Ease of Use & Control

- + Simply plug base unit into power and phone line, charge phone, then dial and talk
- + Features user-friendly telephone style controls
- + Speed dial stores 10 frequently dialed numbers
- + Recording output on base unit connects to a recording device to capture both sides of the conversation
- + Both phones can be operated using the dial pad of either phone
- + MAXAttach Wireless phones can be operated using the dial pad of either phone - dialing, mute, volume controls, etc.

> ROOM APPLICATIONS

MAXAttach Wireless comes with two wireless phones that connect to a single base unit, providing expanded coverage in medium-sized rooms.



> SPECIFICATIONS

Echo Cancellation

Tail time: 60 ms x 3

Noise Cancellation

Dynamic noise cancellation

Telephone Connection

Analog PBX or PSTN line
RJ-11C, -12 dBm nominal

Radio Frequency

2.4 GHz WDCT

Keypad

Alphanumeric standard keypad

Loudspeaker

Volume: 90d Bspl A weighted @ 1 ft
Bandwidth: 200 Hz–3.3 kHz

Record Output

Connector: 2.5 mm mono audio jack
Impedance: < 1000 ohms
Bandwidth: 200Hz–3.3kHz
Dynamic range: 60dB
THD <.01%

Certifications

FCC part 15/CES-003 Class A
FCC part 15 Subpart C/RSS-210
FCC part 68/IC CS-03
CE
UL Certified

Power

Phone unit:
Custom battery pack with nickel metal hydride
batteries, 7.2 V 2200 mAh
12 hours continuous talk time (typical)
36 hours standby
Base unit:
Auto-adjusting power module;
100-240 VAC; 50/60Hz

Wireless Range

Standard WDCT units: 150 ft (45 m)
EU WDCT unit: 50 ft (15 m)

Note: these ranges depend on environmental factors and may vary. The EU unit has a shorter range due to regulatory restrictions on power output in the 2.4 GHz frequency band in the EU.

Environmental

Operating temperature: 32–122° F (0–50° C)
Storage temperature: 41–158° F (5–70° C)
Operating humidity: 15 to 80%
Storage humidity: 10 to 90%

Dimensions (W x D x H)

Phone unit:
10.5" x 10.5" x 3" (26.7 cm x 26.7 cm x 7.6 cm)
Base unit:
4.25" x 5.5" x 2.5" (10.8 cm x 14 cm x 6.4 cm)

Weight

Phone unit: 2.7 lb (1.2 kg)
Base unit: .6 lb (0.27 kg)
Shipping: 12 lb (5.5 kg)

MAXAttach Wireless Includes

Wireless phone units (2)
Base unit (1)
Battery packs (2)
Power supply/chargers (2)
Power supply retainers (2)
Telephone cable
Documentation CD
Quick start guide

PART NUMBERS

MAXAttach Wireless (WDCT)

910-158-070 (North America)
910-158-071 (South Korea)
910-158-072 (Hong Kong/Singapore)
910-158-073 (China)
910-158-074 (Australia/New Zealand)
910-158-075 (South Africa)

MAXAttach Wireless (WDCT for EU)

910-158-276-00 (Europe/UK)

> CLEARONE LOCATIONS

Headquarters:

Salt Lake City, UT USA
5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116
Tel: 801-975-7200
800-945-7730
Fax: 801-977-0087
sales@clearone.com

Latin America

Tel: 801-974-3621
global@clearone.com

EMEA

Tel: 44 (0) 1189 036 053
global@clearone.com

APAC

Tel: 801-303-3388
global@clearone.com