

UB-5825

Panaboard

USB PC Interface
15 seconds per sheet copy speed
includes 1 roll of thermal transfer film,
Includes 3 markers, 1 eraser
Two-Panel Operation



Metallic Electronic Copyboard

null

Input

Panel Dimension (mm)

Height	900.0
Width	1762.0
Panel Surface	2
Scanning System	Image sensor

Output

Printing System	Fusion thermal transfer type
Copy Paper	Standard or recycled paper
Copy Paper Size	A4
Copy Density	203 dpi
Copy Colour	Black
Copy Speed	15s/sheet
Continuous Copies	1 to 9
Contrast Adjustment	Two levels: Normal/Dark
2-screen Compress Copying	yes

System Requirements

Computer	IBM® PC/AT or compatible machine with a CD-ROM drive
----------	--

CPU	Pentium®11 or higher processor
Interface	USB 1.1 (B connector)
OS	Windows® 98/Me/2000/XP
Memory	64 MB or more (Windows® 98/Me) 128 MB or more (Windows® 2000) 256 MB or more (Windows® XP)
HDD	At least 40 MB free space (except saving space for image file)

General

Dimensions (mm)

Width	1735.0
Depth	212.0
Height	1344.0
Weight (kg)	27.0

Power Supply

Herz (Hz)	50 - 60 Hz
Voltage (V)	AC 100-120V or AC 220-240V

Power Consumption

Operational	1.40 A (AC 100-120V) 0.75 A (AC220-240V)
--------------------	--

Operating Environment

Temperature	10-35 degrees C
Humidity	30-80% RH
Standard Accessories	Markers (black,red,blue) Eraser Software CD-ROM Installation manual Operating Instructions Wall mount kit (Upper, lower)