

UB-7325

Panaboard

Plain paper technology
4 panels - including projector panel
USB PC Interface
15 seconds per sheet copy speed
Software included



Electronic Copyboard

null

Input

Panel Dimension (mm)

Height	1400.0
Width	900.0
Panel Surface	4 (endless type)
Scanning System	Contact Image Sensors

Output

Printing System	Fusion Thermal Transfer Type
Copy Paper	Standard or recycled paper
Copy Paper Size	A4
Copy Density	203 dpi
Copy Colour	Black
Copy Speed	15 seconds per sheet
Continuous Copies	Up to 9
Contrast Adjustment	Two levels: Normal / Dark
2-screen Compress Copying	no

System Requirements

Computer	IBM® PC/AT or compatible machine with a CD-ROM drive
----------	--

CPU	Pentium® II or higher processor
Interface	USB 1.1
OS	Windows® 98, Windows® Me, Windows® 2000, Windows® XP
HDD	At least 40 MB free space

General

Dimensions (mm)

Width	1648.0
Depth	264.0
Height	1396.0
Weight (kg)	42.0

Power Supply

Herz (Hz)	50/60 Hz
Voltage (V)	AC 100-120V or AC 220-240V

Power Consumption

Operational	1.40 A (AC 100-120V) 0.75 A (AC 220-240V)
Standby mode	0.2 A (AC 100 - 120 V)

Operating Environment

Temperature	10-35 degrees C
Humidity	30-80% RH
Standard Accessories	Markers (One black, red and blue) Eraser Printer Driver Document Manager and Document Viewer Software Thermal Transfer Film and 20 A4 Size Test Sheets