PJD6531w

HIGH BRIGHTNESS WXGA PROJECTOR

120HZ AND 3D-READY

Broaden your vision.

The ViewSonic® PJD6531w is a wide format 120Hz / 3D-ready DLP® projector which includes BrilliantColor™ technology to produce more vibrant colors, while the high brightness and contrast ratios make this projector shine in virtually any lighting situation. It delivers 3000 lumens with a 1280x800 WXGA native wide resolution. Ideal for classrooms, living rooms or board rooms. Show any true 16:9 content without distortion or scaling. This projector is designed for table-top use or can be mounted on the ceiling for classrooms and meeting rooms. The top load lamp and filter-less design provide for easy maintenance and low total cost of ownership. RJ-45 connectivity enables remote network control, while the extensive input options and integrated 10W speakers give amazing multimedia performance and effective presentations or classroom lessons.



VERSATILE, IMPACT ANYWHERE

- > True 16:9 resolution for widescreen brilliance
 Perfect for wide notebook to screen or even DVDs
 and PC games no distortion or scaling.
- > Network control through RJ-45 Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector lamp status.
- > Bright in virtually any setting with 3,000 lumens With 3200:1 contrast ratio, it's the bright choice for mobile presenters.
- > BrilliantColor™ technology

Latest BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.

> Closed captioning

Integrated closed captioning decoder for the hearing impaired.

- > Give Greener presentations and save
 Use the Eco mode to achieve lower power consumption, reduce overall noise and extend lamp life. Filter less design saves costs and maintenance.
- Stay connected Supports multiple video timing formats from SD (NTSC & PAL) to HD 720p, 1080i/p.















PJD6531w

HIGH BRIGHTNESS WXGA PROJECTOR - 120HZ AND 3D-READY







Optional Accessories

> Replacement Lan	np	RLC-049
> Universal Ceiling	Mount Kit	WMK-005
> Wireless G Preser	ntation Gateway	WPG-350
> Extended Expres	c Evchango®	DDIEE 08 03

	ection ance	٧	4:3 Screen Size Wide Tele		
M	Feet	M	Inches	M	Inches
1.5	4.92	1.17	46.14	0.99	39
1.8	5.90	1.41	55.36	1.18	47
2	6.56	1.56	61.52	1.32	52
3	9.84	2.34	92.27	1.97	78
5	16.40	3.91	153.79	3.29	130
10	32.80	7.81	307.58	6.58	259









ViewSonic Corporation's QMS & EMS have been registered

DISPLAY	Туре	0.55" Digital Micromirror Device (DLP™)		
5	Resolution	WXGA 1280x800		
	Lens	1.2× Manual optical zoom / Manual optical focus		
	Keystone	Vertical digital keystone correction: +/- 40 degrees		
	Size	27"-300" / 0.69m-7.6m		
	Throw Distance	1.2m-10m / 3.9ft-32.8ft		
	Throw Ratio	1.7:1–2.1:1		
	Lamp	230 watt		
	Lamp Life (Normal / Eco-mode)	4000 / 6000* hours		
	Brightness	3000 Lumens		
	Contrast Ratio	2000:1 (typ), 3200:1 (dynamic)		
	Aspect Ratio	4:3, 16:9 and 16:10 (native)		
NIDUT CICNIAL	Color Gamut	70% NTSC 1931 CIE		
INPUT SIGNAL	Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p		
		and 576p (24fps, 25fps and 30fps), HD 720p, 1080i and 1080p (24fps, 25pfs and 30fps)		
	Frequency	Fh: 31–80KHz, Fv: 50–120Hz		
COMPATIBILITY	PC	VGA to UXGA		
	Mac [®]	Up to 1152x864 (scaled)		
CONNECTOR	RGB Input	15-pin mini D-sub (x2)		
	RGB Output	15-pin mini D-sub		
	Digital Input	HDMI 1.3		
	Component	15-in mini -D-Sub (shared with RGB) (x2)		
	Composite Input	RCA jack		
	S-video Input	4-pin mini-DIN		
	Audio Input	3.5mm mini jack		
	Audio Output	3.5mm mini jack		
	Control	RS-232 (9 Pin D-sub)		
	Network	RJ-45		
AUDIO	Speaker	5W (x2)		
POWER	Voltage	90~240VAC (Auto Switching), 50/60Hz (universal)		
	Consumption	305W (typ) / <1W (stand-by mode)		
CONTROLS	Basic	Power, keystone/arrow keys, left/blank, menu/exit,		
00.11.11.025	24316	right/panel key lock, auto, mode/enter, source		
	OSD	Picture: Brightness, Contrast, Color Setting, Keystone,		
		Aspect Ratio, Image, White Intensity, Gamma, 3D Sync, 3D Sync Invert		
		Computer Image: Frequency, Tracking, H Position, V Position		
		Video Image: Saturation, Sharpness, Tint		
		Audio: Volume, Mute, HDMI		
		Setting: Manual Position, Projection, Signal Type, Lamp		
		Hour, Lamp Hour Reset, Filter Mode, Filter Hours, Filter		
		Hours Reset, Power Saving, Auto Source, ECO Mode, High		
		Altitude, OSD Timeout		
		Advance: Blank Screen, Password Word, Screen Capture,		
		Start up Screen, Text Shot, Digital Zoom, DCR, Close		
		Captions, Brilliant Color		
OPERATING	Temperature	41°F-104°F (0°C-40°C)		
CONDITIONS	Humidity	5%–85% (non-condensing)		
NOISE LEVE	Altitude	0~6,000 ft (1,800m), operational up to 10,000 ft (3048m)		
NOISE LEVEL	Normal / Eco-mode	34dB / 29dB		
DIMENSIONS	Physical	11 × 4.5 × 8.6 (in) / 280 × 114 × 218 (mm)		
(W x H x D)	Packaging	13.6 × 8.7 × 12 (in) / 345 × 220 × 305 (mm)		
WEIGHT	Net	5.9 lb. (2.7 kg)		
REGULATIONS		CB, RoHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM		
		(Argentina), NOM, PSB, C-tick, EK, CE, TUV/GS, GOST-R,		
		Hygienic, SASO UKrSEPRO, CCC		
PACKAGE CONT	TENTS	ViewSonic projector, power cable, VGA cable, remote		
		control with laser, lens cap, soft case, Quick Start		
		Guide, ViewSonic Wizard DVD (with User Guide)		
WARRANTY		3-year limited warranty on parts, 1-year limited warranty		

Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved [14976-008-04/10] PJD6531w-1



on lamp, 1st year Express Exchange® service.